


KU-T 1/8 tool-less Cat.5e

RJ45 module, unshielded, Category 5e



KU-T 1/8 tool-less RJ45 module, unshielded, Cat.5e, in white or black

Description

For the transmission of digital and analogue voice, video and data signals. Suitable for all Class D applications respectively Class E Channels in accordance with ISO/IEC 11801, EN 50173-1 and TIA/EIA 568-B.2-10. Housing made of high-impact resistant, flame retardant compound, UL94V-0 rated, with Keystone mounting clip. Contact spring with phosphor bronze alloy, plated with gold. IDC made of phosphor bronze alloy. Information: Suitable for the same faceplates and surface mount boxes as Datwyler's shielded Keystone modules (KS-T).

Proprietà generali

Installation temperature	-10 °C - +60 °C
Operating temperature	-20 °C - +60 °C
Storage temperature	-40 °C - +70 °C

Proprietà elettriche

EMC	unshielded
Gbit/s	Up to 1 Gbit/s

Proprietà meccaniche

Connection type	Connettori a perforazione di isolante IDC
Solid copper wire	0.40 (AWG 26) - 0.65 (AWG 22)
Stranded copper wire	AWG26
Diameter over Insulation	0.70 mm - 1.40 mm
Re-connection	for AWG 22, AWG 23 and AWG 24 quando si usa lo stesso filo o un diametro maggiore
Re-usable	una volta

Standards

Cat./Class	Cat.5e / Class D
Connector standards	IEC 60603-7-2
Cabling standards	ISO/IEC 11801, EN 50173-1, TIA/EIA 568-x

Versions

Numero Materiale	Product	Colore	Peso [kg]	Packing unit
418072	RJ45 module KU-T 1/8 tool-less, Cat. 5e, unshielded	bianco	0,01 kg	10 pcs.
418073	RJ45 module KU-T 1/8 tool-less, Cat. 5e, unshielded	nera	0,01 kg	10 pcs.

