

UP/UP-K Faceplate 1x, 2x, 3x

flush/duct mounted

for 1, 2 or 3 modules with Keystone fitting, angled outlet

GERMAN STANDARD



1

1 1-port faceplate, angled outlet



2

2 2-port faceplate, angled outlet



3

3 3-port faceplate, angled outlet

Description

Faceplates applicable for the installation of 1, 2 or 3 modules with Keystone fitting.

The modules are easily fitted into the faceplates.

Integrated dust shutters.

The central plate has a labelling field with transparent cover.

On metallic support frame, an additional grounding connection is available.

Delivered without modules.

Application

Suitable for the following Datwyler modules:

- PS-GG45 7A 4P shielded
- RJ45 module KS-T Plus 1/8 Cat. 6A shielded
- RJ45 module KS-TC Plus Cat.6A (IEC), shielded
- RJ45 module KU Plus 1/8 Cat.6A unshielded
- RJ45 module KS-TS 1/8 Cat. 6/EA shielded
- RJ45 module KS-T 1/8 Cat. 6/EA shielded
- RJ45 module KU-T 1/8 Cat. 6 / Cat. 5e unshielded

Note

3-port faceplate not compatible with switch range (designs) of other vendors.

Versions

Material number	Product	Colour	Weight [kg]	Packing unit
185866	UP-K Faceplate for 1 module with Keystone snap-in fitting, angled	pure white	0.08 kg	1 pc.
185867	UP-K Faceplate for 2 modules with Keystone snap-in fitting, angled	pure white	0.08 kg	1 pc.
185869	UP-K Faceplate for 3 modules with Keystone snap-in fitting, angled	pure white	0.05 kg	1 pc.

Subject to technical modification

As of 2020-10-22 06:48:17