


## FO Outdoor wbKWT HP / A-DQ(ZN)(SR)2Y

HighP Euroclass Fca

dry interstices, longitudinally watertight,  
corrugated steel tape, rodent proof



- 1 ≤ 24 fibres
- 2 Loose tube
- 3 Swelling tape
- 4 Aramid yarn
- 5 Ripcord
- 6 Corrugated steel tape
- 7 HDPE sheath



### Description

Robust fibre optic outdoor cable with multiple loose tubes.  
Installation friendly dry construction.  
Rodent proof due to corrugated steel tape.  
High tensile strength, easy to lay.  
Optimised for installation in and blowing into ducts.

### Applicazione

For pulling in or blowing through ducts.  
Suitable for laying in cable platforms, cable shafts and even in complex cable trays,  
particularly where a reliable rodent protection is required.  
Direct burial.

### Costruzione

Armatura (protezione per roditori)	rodent proof
Outer sheath material	PE

## Proprietà generali

Impronta	DATWYLER «cable type» «Datwyler designation» «DIN designation» «no. of fibres» «fibre type» «add. text» «batch no.» «meter marks»
Installation temperature	-10 °C - +50 °C
Integrità del circuito	No
Operating temperature	-40 °C - +70 °C
Storage temperature	-40 °C - +70 °C

## Standards

Tensile performance	IEC 60794-1-21 E1
Crush resistance	IEC 60794-1-21 E3
Impact	IEC 60794-1-21 E4
Repeated bending	IEC 60794-1-21 E6
Torsion	IEC 60794-1-21 E7
Bend	IEC 60794-1-21 E11
Water penetration	IEC 60794-1-22 F5
Reaction to fire (Euroclasses)	EN 13501-6: F <sub>ca</sub>
Zero halogen no corrosive gases	IEC 60754-1/-2, EN 60754-1/-2, VDE 0482-754-1/-2

## Versions

Numero Materiale	Product	Reaction To Fire	Outer sheath colour	Fibre type	Diametro esterno della guaina [mm]	Raggio di curvatura [mm]	Weight [kg\ km]	Tensile load [N]	Crush resistance short term [N]	Crush resistance continuous [N]	Fire load [kWh\m]	Packing unit
19018400FZ	FO Outdoor HP 2x12	Fca	nera	E9/125 G.652.D OS2	13,4	200	145	2.500	4.000	1.500	1,019	al metro
19608000FZ	FO Outdoor HP 2x12	Fca	nera	G50/125 OM3	13,4	200	145	2.500	4.000	1.500	1,019	al metro
19018500FZ	FO Outdoor HP 4x12	Fca	nera	E9/125 G.652.D OS2	13,4	200	145	2.500	4.000	1.500	1,019	al metro
18659000FZ	FO Outdoor HP 5x12	Fca	nera	E9/125 G.652.D OS2	13,4	200	145	2.500	4.000	1.500	1,019	al metro
19065000FZ	FO Outdoor HP 6x12	Fca	nera	E9/125 G.652.D OS2	13,4	200	149	2.500	4.000	1.500	1,019	al metro
19169800FZ	FO Outdoor HP 4x24	Fca	nera	E9/125 G.652.D OS2	13,6	205	167	2.500	4.000	1.500	1,094	al metro
19119700FZ	FO Outdoor HP 6x24	Fca	nera	E9/125 G.652.D OS2	13,6	205	170	2.500	4.000	1.500	1,094	al metro