

FL – Low Fire Hazard – unsupported

Low rise - travelling height maximum 80m



Drawing according to article number 191113 - Type 8582-F



Beschrijving

Elevator suspension cable for indoor and panoramic elevators.

Toepassing

To comply with the correct installation procedures please refer to the Datwyler installation manual which is available separately

Constructie

Ader isolatie	low fire hazard
Buitenmantel	low fire hazard
Core flexibel	class 5
Mantelkleur	zwart
Ondersteunende leden	none

Algemene eigenschappen

Bedrijfstemperatuur	-15 °C - +70 °C
Coax	zwart
Kern	black, white numbered, G = with green-yellow core(s)
Pair/quad	various colours or black with white numbers

Elektrische eigenschappen

Nominale spanning Uo/U	according to table
------------------------	--------------------

Mechanische eigenschappen

Aanbevolen lusdiameter	according to table, tolerance -50/+100 mm
Maximale loopsnelheid	4 m/s
Maximale reishoogte	80 m
Maximale vrije schorsing	45 m
Versnelling	0,8 m/s ²

Normen / Standards

Standaard voor flexibele besturingskabels voor liften	EN 50214
---	----------

Versions

Materiaal nummer	Artikel	Mantelkleur	Cu tarief [kg/km]	Gewicht [kg/km]
191110	8511-F	zwart	87	259
185125	8511-F	zwart	130	382
191112	8511-F	zwart	173	511
191111	8636-F	zwart	123	420
182205	8827-F	zwart	244	735
191113	8582-F	zwart	306	958
190491	8582-F	zwart	149	524

Onder voorbehoud van technische wijziging

Vanaf 2020-12-03 13:11:28