

## Rack lighting 19"


1U

with door contact (optional)



1

1 19"/1U lighting with LED, 230 or 110-240 V



3

2

2 Door position contact TPC, straight  
3 Blind frame BL, light grey

### Description

Lighting with LED, AC 230 V, 7.2 W, 945 lm

Dimensions: 448 x 54.5 x 26 mm

Colour: light grey (RAL 7035) or black (RAL 9005)

Connection cable: 2 x 0.75 mm<sup>2</sup>, L = 3000 mm, black, free ends with sleeves

Socket: 2p., for door position contact TPC (straight or angled)


Material: PC/ABS

Protection degree: IP20/II

Mounting system: variable; mount in 19" frame: via built in swing mounting links (tool-less)

Designed for variable mounting: via built in swing mounting links (tool-less), magnetic and/or with screws.

Right image: mounting of door position contact TPC.



### Applicazione

IT racks and technical rooms in data centres and FTtx installations

### Proprietà generali

Average life span	50,000 hr
Illuminant	Hi Power LED
Luminous colour	White, 5600 K
Operating temperature	-20 °C - +50 °C
Storage temperature	-20 °C - +60 °C
Umidità atmosferica	80 %

### Proprietà elettriche

Current	0,080 A
Energy consumption	9 kWh/1000h
Power consumption	7,2 W

## Scope of delivery

Lighting, single pack, with mounting material and installation instruction

## Standards

CE certified	Yes
Directives	2014/35/EU and 2014/30/EU (all types)
Energy efficiency class	A

## Versions

Numero Materiale	Product	Colore	Tensione nominale AC	Peso [kg]
280504	LED 19" 1U 230V / 7.2W S DC 3m GR	grigio chiaro	AC 230 V	0,48 kg
280505	LED 19" 1U 230V / 7.2W S DC 3m BK	nera	AC 230 V	0,48 kg
280510	BL 19" 1U Frame GR	grigio chiaro		0,1 kg
280509	TPC 230V 1.5m ST BK	nera	AC 230 V	0,2 kg
280511	BL 19" 1U Frame BK	nera		0,1 kg

Con riserva di modifiche tecniche

A partire da 2021-01-27 11:42:12