

FO patch panel OV-S

19"/1U, Breakout box OV-S, E9/125 OS2

with adapters



Breakout box OV-S, 19"/1U, extractable, configuration example with 6 SCD adapters

Description

For the termination of pre-assembled fibre optic cables - maximum of 96 fibres. Loaded with a maximum of 12 / 24 FO adapters.

Proprietà generali

Alloggiamento	metal sheet, black, extractable drawer with locking mechanism, box allows for depth-adjustable mounting (5 steps, maximum 50 mm)
Capacità	up to 96 fibres
Dimensioni	19"/1U
Impronta	numbers (silk screen printing) on frontplate
Ingresso cavi	rear left and right with pre-stamped cable entries M15, M20 and M25 - these pre-stamped holes can be opened as necessary
Piastra frontale	similar to RAL 7035, similar to RAL 9005 or stainless steel
Scarico della trazione	with cable tie and screwed cable gland (M20)

Proprietà ottiche

Tipologia di fibra	E9/125 OS2
--------------------	------------

Proprietà meccaniche

Adattatore	SCD, LCD, LCQ, LSH Coloured Polymer housings or ST metal housings, ceramic sleeves
------------	--

Scope of delivery

Breakout box with
 - two straight cable entries
 - FO adapters, fastened by screws

Versions

Numero Materiale	Product	Colour (Front-plate)	Number of adapters	Adapter	Colour (Adapter)	Orientamento adattatore	Dimensioni esterne	Classe della fibra	Peso [kg]	Packing unit
41542300ZY	Breakout box OV-S 6xLCD, OS2	nera	6	LCD	blu	offset horizontal	1 U, x 19 in x 245 mm	OS2	2,6 kg	1 pc.
41525000ZY	Breakout box OV-S 6xLCD, OS2	grigio chiaro	6	LCD	blu	offset horizontal	1 U, x 19 in x 245 mm	OS2	2,6 kg	1 pc.
41542400ZY	Breakout box OV-S 12xLCD, OS2	nera	12	LCD	blu	offset horizontal	1 U, x 19 in x 245 mm	OS2	2,6 kg	1 pc.

Numero Materiale	Product	Colour (Front-plate)	Number of adapters	Adapter	Colour (Adapter)	Orientamento adattatore	Dimensioni esterne	Classe della fibra	Peso [kg]	Packing unit
41545100ZY	Breakout box OV-S 12xLCD, OS2	nera	12	LCD	blu	angled	1 U, x 19 in x 245 mm	OS2	2 kg	1 pc.
41525400ZY	Breakout box OV-S 12xLCD, OS2	grigio chiaro	12	LCD	blu	offset horizontal	1 U, x 19 in x 245 mm	OS2	2,6 kg	1 pc.
41534200ZY	Breakout box OV-S 24xLCD, OS2	nera	24	LCD	blu	offset horizontal	1 U, x 19 in x 245 mm	OS2	2,6 kg	1 pc.
41525800ZY	Breakout box OV-S 24xLCD, OS2	grigio chiaro	24	LCD	blu	offset horizontal	1 U, x 19 in x 245 mm	OS2	2,6 kg	1 pc.
41540100ZY	Breakout box OV-S 8xLCQ, OS2	nera	8	LCQ	blu	vertical	1 U, x 19 in x 245 mm	OS2	1 kg	1 pc.
41545700ZY	Breakout box OV-S 12xLCQ, OS2	nera	12	LCQ	blu	angled	1 U, x 19 in x 245 mm	OS2	2 kg	1 pc.
41540000ZY	Breakout box OV-S 24xLCQ, OS2	nera	24	LCQ	blu	vertical	1 U, x 19 in x 245 mm	OS2	1 kg	1 pc.
41520700ZY	Breakout box OV-S 24xLCQ, OS2	grigio chiaro	24	LCQ	blu	vertical	1 U, x 19 in x 245 mm	OS2	1 kg	1 pc.
41545900ZY	Breakout box OV-S 6xLCD/ APC, OS2	nera	6	LCD/APC	verde	offset horizontal	1 U, x 19 in x 245 mm	OS2	2,6 kg	1 pc.
41544400ZY	Breakout box OV-S 6xLCD/ APC, OS2	grigio chiaro	6	LCD/APC	verde	offset horizontal	1 U, x 19 in x 245 mm	OS2	2,6 kg	1 pc.
41545800ZY	Breakout box OV-S 12xLCD/ APC, OS2	nera	12	LCD/APC	verde	offset horizontal	1 U, x 19 in x 245 mm	OS2	2,6 kg	1 pc.
41544500ZY	Breakout box OV-S 12xLCD/ APC, OS2	grigio chiaro	12	LCD/APC	verde	offset horizontal	1 U, x 19 in x 245 mm	OS2	2,6 kg	1 pc.
41512500ZY	Breakout box OV-S 24xLCD/ APC, OS2	nera	24	LCD/APC	verde	offset horizontal	1 U, x 19 in x 245 mm	OS2	2,6 kg	1 pc.
41511900ZY	Breakout box OV-S 24xLCD/ APC, OS2	grigio chiaro	24	LCD/APC	verde	offset horizontal	1 U, x 19 in x 245 mm	OS2	2,8 kg	1 pc.
41540700ZY	Breakout box OV-S 6xSCD, OS2	nera	6	SCD	blu	vertical	1 U, x 19 in x 245 mm	OS2	2,5 kg	1 pc.
41526200ZY	Breakout box OV-S 6xSCD, OS2	grigio chiaro	6	SCD	blu	vertical	1 U, x 19 in x 245 mm	OS2	2,5 kg	1 pc.
41540800ZY	Breakout box OV-S 12xSCD, OS2	nera	12	SCD	blu	vertical	1 U, x 19 in x 245 mm	OS2	2,5 kg	1 pc.
41526600ZY	Breakout box OV-S 12xSCD, OS2	grigio chiaro	12	SCD	blu	vertical	1 U, x 19 in x 245 mm	OS2	2,7 kg	1 pc.
41540900ZY	Breakout box OV-S 24xSCD, OS2	nera	24	SCD	blu	vertical	1 U, x 19 in x 245 mm	OS2	2,5 kg	1 pc.
41527000ZY	Breakout box OV-S 24xSCD, OS2	grigio chiaro	24	SCD	blu	vertical	1 U, x 19 in x 245 mm	OS2	2,8 kg	1 pc.
41531900ZY	Breakout box OV-S 6xLSH/ APC, OS2	grigio chiaro	6	LSH/APC	verde	vertical	1 U, x 19 in x 245 mm	OS2	2,3 kg	1 pc.
41532100ZY	Breakout box OV-S 12xLSH/ APC, OS2	grigio chiaro	12	LSH/APC	verde	vertical	1 U, x 19 in x 245 mm	OS2	2,6 kg	1 pc.
41532300ZY	Breakout box OV-S 24xLSH/ APC, OS2	grigio chiaro	24	LSH/APC	verde	vertical	1 U, x 19 in x 245 mm	OS2	2,7 kg	1 pc.

Numero Materiale	Product	Colour (Front-plate)	Number of adapters	Adapter	Colour (Adapter)	Orientamento adattatore	Dimensioni esterne	Classe della fibra	Peso [kg]	Packing unit
41511800ZY	Breakout box OV-S 24xLSH-C/ APC, OS2	grigio chiaro	24	LSH-C/APC	verde	vertical	1 U, x 19 in x 245 mm	OS2	2,7 kg	1 pc.

.....
Variants on request.

Con riserva di modifiche tecniche

A partire da 2021-02-23 14:59:58