

HD-DCS modular panels, 19"/1U

to take 4 or 12 HD-DCS plug-in modules



Description

Sturdy stainless steel housing with depth-adjustable cable support plate and front 19"/1U mounting brackets.

Pre-assembled with four slots to take HD-DCS plug-in modules from the front or rear. Each slot accepts three plug-in modules with 6 ports or one plug-in module with 12 or 24 ports.

Allows for variable, scalable port densities from 48 up to 96 ports (LCD and MPO/MTP*).

Application

Modular, scalable high-density platform for the data centre environment.

Variable port densities of up to 96 LCD and/or MPO ports on one rack unit (U). This allows for up to 192 fibres (with LCD) or 1152 fibres (with MPO₁₂) per height unit.

Propriétés générales

Capacité

12 plug-in modules with 6 LCD or MPO ports
4 plug-in modules with 12 LCD or MPO ports
4 plug-in modules with 24 LCD or MPO ports

Scope of delivery

19"/1U panel (19" mounting brackets) with integrated, depth-adjustable cable support plate (without plug-in modules)

2 cover plates with label strips

19" mounting material

Accessories such as strain relief clips and cable mounting clips to be ordered separately.

Versions

Numéro de matériau	Produit	Couleur (panneau avant)	Dimensions extérieures	Couleur	Poids [kg]	Unité d'emballage
473600	HD-DCS panel 19" 1U, 4x 12/24-port	noire	1 U44.2 mm x 483 mm x 432.1 mm	argentés	2,25 kg	1 pc.
473601	HD-DCS panel 19" 1U, 12x 6-port	noire	1 U44.2 mm x 483 mm x 432.1 mm	argentés	2,25 kg	1 pc.
473602	HD-DCS panel 19" 1U, 6/12/24-port	noire	1 U44.2 mm x 483 mm x 432.1 mm	argentés	2,25 kg	1 pc.

MTP* is a registered trade name of US Conec.