

## FO patch panel OV-S

19"/1U, Splice box OV-S, G50/125 OM5

with adapters and pigtails



Fibre optic splice box OV-S, 19"/1U, extractable, configuration example with 24 LCD adapters and 48 pigtails

### Description

For the termination of fibre optic cables - maximum of 96 fibres.  
Loaded with FO adapters, ready for splicing, with prepared pigtails (per 2 m, colour code: IEC 60304).

### Proprietà generali

|                        |  |
|------------------------|--|
| Alloggiamento          | metal sheet, black, extractable drawer with locking mechanism, box allows for depth-adjustable mounting (5 steps, maximum 50 mm) |
| Capacità               | up to 96 fibres  |
| Dimensioni             | 19"/1U   |
| Impronta               | numbers (silk screen printing) on frontplate   |
| Ingresso cavi          | rear left and right with pre-stamped cable entries M15, M20 and M25 - these pre-stamped holes can be opened as necessary         |
| Piastra frontale       | similar to RAL 7035, similar to RAL 9005 or stainless steel  |
| Scarico della trazione | with screwed cable gland   |

### Proprietà ottiche

|                    |             |
|--------------------|-------------|
| Tipologia di fibra | G50/125 OM5 |
|--------------------|-------------|

### Scope of delivery

- Splice box with
- two straight cable entries
  - one screwed cable gland M20
  - coloured pigtails with measurement report
  - FO adapters, fastened by screws
  - splice trays with cover
  - splice holder for 12 x crimp splice protectors
  - Delivery without splicing protection

### Versions

| Numero Materiale | Product                     | Colour (Front-plate) | Number of adapters | Adapter | Colour (Adapter) | Orientamento adattatore | Dimensioni esterne    | Pigtails | Classe della fibra | Peso [kg] | Packing unit |
|------------------|-----------------------------|----------------------|--------------------|---------|------------------|-------------------------|-----------------------|----------|--------------------|-----------|--------------|
| 41513900ZY       | Splice box OV-S 6xLCD, OM5  | grigio chiaro        | 6                  | LCD     | lime green       | offset horizontal       | 1 U, x 19 in x 245 mm | 12 x LC  | OM5                | 2,5 kg    | 1 pc.        |
| 41514000ZY       | Splice box OV-S 6xLCD, OM5  | nera                 | 6                  | LCD     | lime green       | offset horizontal       | 1 U, x 19 in x 245 mm | 12 x LC  | OM5                | 2,5 kg    | 1 pc.        |
| 41514100ZY       | Splice box OV-S 12xLCD, OM5 | grigio chiaro        | 12                 | LCD     | lime green       | offset horizontal       | 1 U, x 19 in x 245 mm | 24 x LC  | OM5                | 2,5 kg    | 1 pc.        |

**DATWYLER**

| Numero Materiale | Product                     | Colour (Front-plate) | Number of adapters | Adapter | Colour (Adapter) | Orientamento adattatore | Dimensioni esterne    | Pigtails | Classe della fibra | Peso [kg] | Packing unit |
|------------------|-----------------------------|----------------------|--------------------|---------|------------------|-------------------------|-----------------------|----------|--------------------|-----------|--------------|
| 41514200ZY       | Splice box OV-S 12xLCD, OM5 | nera                 | 12                 | LCD     | lime green       | offset horizontal       | 1 U, x 19 in x 245 mm | 24 x LC  | OM5                | 2,5 kg    | 1 pc.        |
| 41514300ZY       | Splice box OV-S 24xLCD, OM5 | grigio chiaro        | 24                 | LCD     | lime green       | offset horizontal       | 1 U, x 19 in x 245 mm | 48 x LC  | OM5                | 2,5 kg    | 1 pc.        |
| 41514400ZY       | Splice box OV-S 24xLCD, OM5 | nera                 | 24                 | LCD     | lime green       | offset horizontal       | 1 U, x 19 in x 245 mm | 48 x LC  | OM5                | 2,5 kg    | 1 pc.        |

Variants on request.

Con riserva di modifiche tecniche

A partire da 2021-05-07 10:19:09