


## Fibre pigtail 1 m

E9/125 G.657.A1 OS2, APC Version



### Description

Semi tight buffer, 600 µm

### Optical Properties

Connector grade (better than)	B1
Ferrule material	Zirkonia
Fibre type	E9/125 G.657.A1 OS2
Insertion loss (IL), maximal	0.25 dB
Insertion loss (IL), typical	0.12 dB
Lifetime	1000 connections with stable attenuation values
Reproducibility of the IL	maximal +/- 0.1dB
Return loss (RL), minimal	65 dB
Return loss (RL), typical	70 dB

### Versions

Material number	Product	Fibre type	Weight [kg]	Packing unit
309311	Pigtail LC/APC G.657.A1	E9/125 G.657.A1 OS2	0.1 kg	1 pc.
309312	Pigtail LC/APC G.657.A1	E9/125 G.657.A1 OS2	0 kg	1 pc.
309313	Pigtail LC/APC G.657.A1	E9/125 G.657.A1 OS2	0.1 kg	1 pc.
309314	Pigtail LC/APC G.657.A1	E9/125 G.657.A1 OS2	0.1 kg	1 pc.
309315	Pigtail SC/APC G.657.A1	E9/125 G.657.A1 OS2	0.1 kg	1 pc.
309316	Pigtail SC/APC G.657.A1	E9/125 G.657.A1 OS2	0.1 kg	1 pc.

Subject to technical modification

As of 2021-02-01 07:25:48