

## ODF subracks, Standard

1U, 2U, 3U, 48-144 fibres



High-density subrack for Datwyler ODF, 3U

### Description

The Datwyler ODF subracks are particularly suitable for high-density applications in telco/carrier networks. They provide advanced splice and patch systems and cable management. Smooth and convenient swing-out system. Cable glands to secure the incoming fibres. Strain relief for all cables. Bend radius control for fibres.

### Application

Backbone and distribution networks, particularly for PoPs in the carrier section. Also suitable for data centres and LAN projects (19 ).

### Propriétés générales

Capacité	1U up to 48, 2U up to 96, 3U up to 144 fibres (72 duplex adapters)
Colour	Light grey, RAL 7035 (powder-coated)

### Versions

Numéro de matériau	Produit	Nombre d'adaptateurs	Adaptateurs	Nombre de fibres	Dimensions extérieures	Poids [kg]
19694900ZY	ODF subrack, Standard	24	LCD/APC	48	1 U	6,65 kg
19694800ZY	ODF subrack, Standard	48	LCD/APC	96	2 U	6,4 kg
19694700ZY	ODF subrack, Standard	72	LCD/APC	144	3 U	6,1 kg

Sous réserve de modifications techniques

A partir de 2021-01-27 11:41:57