

ODF subracks, Standard

1U, 2U, 3U, 48-144 fibres



High-density subrack for Datwyler ODF, 3U

Beschrijving

The Datwyler ODF subracks are particularly suitable for high-density applications in telco/carrier networks. They provide advanced splice and patch systems and cable management. Smooth and convenient swing-out system. Cable glands to secure the incoming fibres. Strain relief for all cables. Bend radius control for fibres.

Toepassing

Backbone and distribution networks, particularly for PoPs in the carrier section. Also suitable for data centres and LAN projects (19).

Algemene eigenschappen

Capaciteit	1U up to 48, 2U up to 96, 3U up to 144 fibres (72 duplex adapters)
Colour	Light grey, RAL 7035 (powder-coated)

Versions

Materiaal nummer	Artikel	Antaal Adapters	Adapter	Aantal vezels	Buitenste afmetingen	Gewicht [kg]
19694900ZY	ODF subrack, Standard	24	LCD/APC	48	1 U	6,65 kg
19694800ZY	ODF subrack, Standard	48	LCD/APC	96	2 U	6,4 kg
19694700ZY	ODF subrack, Standard	72	LCD/APC	144	3 U	6,1 kg

Onder voorbehoud van technische wijziging

Vanaf 2021-01-27 11:41:57