

Datwyler Infrastructure Monitoring System

DIMS 300



Descrizione

DIMS 300 is a tried and tested monitoring system which can be used in all branches of industry for the continuous measurement, recording and reporting of performance-critical environmental factors in a rack.

It combines the most advanced hardware and software.

Solid metal housing in 19 inch format.

Internal 230 volt power supply.

8 auto-sensing RJ12 ports for attaching sensors.

Can be extended with additional sensor ports or digital inputs via CAN port.

Alarm messages possible via bistable relays.

Can be integrated into SNMP-compatible management software on request.

Proprietà generali

Umidità atmosferica	5 - 80 %
Storage temperature	-25 °C - +85 °C
Operating temperature	0 °C - +60 °C

Proprietà elettriche

Corrente in ingresso	10 W
Tensione all'ingresso	230 V

Proprietà tecniche

Ingressi sensori analogici	8x RJ12 Ports
Ingressi digitali	12x potential free inputs
Uscite di allarme	2x 12 VDC max. 0,25 A
Uscite a relè	2x relay port NO/NC
Porte CAN	2x CAN open Port (for CAN sensors or extension units)
USB	1x miniAB HS-USB 2.0
Rete	1x 10/100 Mbit/s
Carta SD	1x SD card Slot
Protocolli	DHCP, HTTP, HTTPS, SNMP v1, SNMP v2c, SNMP v3, SNMP TRAP, SNMP GET, SMTP, SSL, FTP, Syslog, TLS, RADIUS
Indicazione LED	Power / ACT, Network activity, 12V Relay status E1 & E2, Error LED, 2x relay status 1&2

Ambito di consegna

1x DIMS 300
1x patch cable RJ45 (1m)
1x IEC C13 230 V AC power supply cable
1x connector plug 3,5mm 3pol.
1x Connector plug 3,81mm 3pol.
1x MiniUSB to USB cable
4x self-adhesive rubber buffers
1x 19" mounting bracket (1 pair)
1x quick start guide

Versioni

Codice art.	Prodotto	Dimensioni esterne	Colore	Peso [kg]	Packing unit
41847300ZY	DIMS 300 incl. LTE Modem	1 U, 44.45 mm x 440 mm x 79.4 mm	nera	1,45 kg	1 pc.

Con riserva di modifiche tecniche

A partire da 2021-12-08 10:45:59