



# TYPE APPROVAL CERTIFICATE

Certificate No:  
**TAE000044A**  
Revision No:  
**1**

## This is to certify:

That the **Category cables**

with type designation(s)  
**CU 7702 4P FLEX SHF1 AWG 26,**  
**CU 7724 4P FLEX SHF1 AWG24**

Issued to

**Dätwyler IT Infra AG**  
**Altdorf, Switzerland**

is found to comply with

**DNV rules for classification – Ships, offshore units, and high speed and light craft**

## Application :

**Work area wiring Cat 7.**

**Products approved by this certificate are accepted for installation on all vessels classed by DNV.**

Issued at **Høvik** on **2023-07-03**

for **DNV**

This Certificate is valid until **2025-10-25**.

DNV local unit: **Augsburg**

Approval Engineer: **Ivar Bull**

.....  
**Frederik Tore Elter**  
**Head of Section**

This Certificate is subject to terms and conditions overleaf. Any significant change in design or construction may render this Certificate invalid. The validity date relates to the Type Approval Certificate and not to the approval of equipment/systems installed.

LEGAL DISCLAIMER: Unless otherwise stated in the applicable contract with the holder of this document, or following from mandatory law, the liability of DNV AS, its parent companies and their subsidiaries as well as their officers, directors and employees ("DNV") arising from or in connection with the services rendered for the purpose of the issuance of this document or reliance thereon, whether in contract or in tort (including negligence), shall be limited to direct losses and under any circumstance be limited to 300,000 USD.



## Product description

Work area wiring CU 7702 4P FLEX SHF1 AWG26,  
 Work area wiring CU 7724 4P FLEX SHF1 AWG24

Conductor	Stranded Bare Copper, AWG 26 or AWG 24
Insulation	Foam PE
Cabling / Individual screen	Twisted pairs with Al-/polyester tape
Overall screen	Tinned copper wire braid
Outer Sheath	SHF1

Number of cores x conductor cross-section	Overall diameter
4 x 2 x 26 AWG	6.4
4 x 2 x 24 AWG	7.6

### Typical measured values

Frequency [MHz]	1	4	10	100	250	500	600	800	862
Attenuation [dB/10m]	0.26	0.5	0.79	2.67	4.3	6.2	6.71	7.9	8.3
NEXT [dB]	100	100	100	100	95	92	90	90	90
ACR-N [dB/10m]	97	97	97	97	92	89	87	87	87
PS-ACR-N [dB/10m]	100	99	99	97	91	86	83	82	82
ACR-F [dB/10m]	97	96	96	94	88	83	80	79	79
PS-ACR-F [dB/10m]	100	99	99	97	95	91	88	87	87
PS ELFEXT [dB]	97	96	96	94	92	88	85	84	84
Return loss [dB]	26	32	35	30	27	24	23	21	21

## Application/Limitation

The requirements of SOLAS Amendments Chapter II-1, Part D, Reg. 45, 5.2 (provision to be taken to limit Fire Propagation along Bunches of Cables or Wires) are fulfilled without any additional measures.

Due to the low cross section of these cables, extra precautions shall be made during installation. In order to achieve a transmission link compliant with Category 7, cables shall be installed with suitable termination equipment according to manufacturer's recommendations.

Work area wiring Cat 7.  
 Flame retardant in bunch; cat C. Low smoke.

Temperature window:  
 Operation: -20°C to +60°C  
 Installation: 0°C to +50°C

## Type Approval documentation

**Specification:** 20201007\_Technische Spezifikation\_CU 7702f SHF1\_V.1.0  
 Data Sheet CU 7702 4P FLEX SHF1  
 Data Sheet CU 7724 4P flex SHF1 dated 2022-10-11

**Test report:** Overview of tests carried out, ref. EXCEL Table  
 "DNVGL TA Check list -overview of electric tests rev.1"  
 Test reports for CU 7724 4P FLEX SHF1 AWG24

## Tests carried out

Standard	Release	General description	Limitation
DNV-CP-0403	2021-09	DNV GL Type approval program for Data communication cables – category cables	Work area wiring tested to IEC 61156-5 Cat 7 except attenuation and conductor resistance
IEC 61156-6	2020-04	Multicore and symmetrical pair/quad cables for digital communications - Part 6: Symmetrical pair/quad cables with transmission characteristics up to 1 000 MHz - Work area wiring - Sectional specification	Attenuation and conductor resistance
IEC 60332-1-2	2015-07	Tests on electric and optical fibre cables under fire conditions – Part 1-2: Test for vertical flame propagation for a single insulated wire or cable –Procedure for 1 kW pre-mixed flame	
IEC 60332-3-24	2018-07	Tests on electric and optical fibre cables under fire conditions – Part 3-24: Test for vertical flame spread of vertically-mounted bunched wires or cables – Category C	.
IEC 60754-2	2019-11	Test on gases evolved during combustion of materials from cables - Part 2: Determination of acidity (by pH measurement) and conductivity	Halogen free: pH > 4,3 Conductivity < 10µS/mm
IEC 61034-1/2	2019-11	Measurement of smoke density of cables burning under defined conditions – Test apparatus, procedure and requirements	Low smoke Light transmittance >60%

## Marking of product

DATWYLER CU 7702 4P FLEX AWG26 S/FTP CAT 7 IEC SHF1 NVP78% - DNVGL-CP-0403 - IEC 61156-6 <CPR-Class> MADE IN SWITZERLAND <Lot-number> <length marking> M

DATWYLER CU 7724 4P FLEX AWG24 S/FTP CAT 7 IEC SHF1 NVP78% -DNV-CP-0403- IEC 61156-6 <CPR-Class> MADE IN SWITZERLAND <Lot-number> <length marking> M

## Periodical assessment

The scope of the periodical assessment is to verify that the conditions stipulated for the Type approval are complied with and that no alterations are made to the product design or choice of materials.

The main elements of the assessment are:

- Inspection on factory samples, selected at random from the production line (where practicable)
- Results from Routine Tests (RT) checked (if not available tests according to RT to be carried out)
- Review of type approval documentation
- Review of possible change in design, materials and performance
- Ensuring traceability between manufacturer's product type marking and Type Approval Certificate.

Periodical assessment is to be performed after 2 years and after 3.5 years. A renewal assessment will be performed at renewal of the certificate.

END OF CERTIFICATE